

OPTFL01-48W



Faretto LED / LED Flood light
Reflektory LED / LED - Scheinwerfer

RoHS



IT / ENG / PL / DE	
Consumo / Power consumption / Zużycie energii / Energieverbrauch	55W
Voltaggio / Input voltage & frequency	AC100~277V 50~60Hz
Napięcie wejściowe i częstotliwość / Eingangsspannung und Frequenz	
Fattore di potenza / Power factor / Współczynnik mocy / Leistungsfaktor	> 90%
Efficienza dei LED / LED efficiency	110~130lm/W
Wydajność LED / Leistungsfähigkeit von LED	
Equivalente a / Equivalent lamp power	55W ≈ 300W
Ekwiwalentna moc / Äquivalente Leistung	
Nr. Led / LED quantity / Ilość LED / Menge von LED	48x1W LED
Colore della luce / Light color / Barwa światła / Lichtfarbe	Bianco, rosso, blu, verde, giallo, ambra, AWB, RGB / white, red, blue, green, yellow, amber, AWB, RGB / biały, czerwony, niebieski, zielony, żółty, bursztynowy, AWB, RGB / weiß, rot, blau, grün, gelb, bernstein, AWB, RGB
Tipo LED / LED type / Typ LED / Typ von LED	Philips Luxeon
Temperatura della luce / Color temperature	3000-3500K/4000-4500K/5000-7000K/7000K
Temperatura barwowa / Farbtemperatur	
Angolo di proiezione / Beam angle	120°x60°; 15°/30°/45°/60°
Kąt rozsyłu światła / Lichtverteilungswinkel	
Durata / Lifetime / Czas użytkowania / Lebensdauer	50.000 h
Riciclabile / Recycling / Recycling / Recykling	Sì / yes / tak / ja
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	65
IK Protezione agli urti / IK rating / Stopień ochrony IK / Schutzart IK	09
ULOR	0%
Temperatura di funzionamento / Operating temperature	-20°C~45°C
Temperatura pracy / Arbeitstemperatur	
Temperatura di magazzino / Storage temperature	-40°C~60°C
Temperatura stowienia / Aufbewahrungstemperatur	
Materiali e finiture / Materials and finishing	Aluminum alloy + glass / Laga di alluminio + vetro temperato / Stop aluminium + szkło hartowane / Cast Aluminum + Glas
Materiały i wykończenie / Materialien und Ausfertigung	Argento / Silver / Srebro / Silber
Colore / Product color / Kolor produktu / Farbe des Fabrikats	A*
Energy label / Energy label	
Etykieta energetyczna / Energieverbrauchskennzeichnung	
Dimensioni / Product dimensions	320x196x270mm
Wymiary produktu / Abmessungen des Fabrikats	
Lumen / Total Lumens	4250lm
Całkowita ilość lumenów / Gesamte Menge von Lumen	
CRI / Color Rendering Index	75 Ra
Współczynnik oddawania barw / Farbwiedergabeindex	
Efficienza alimentatore / Power Supply Efficiency	>85%
Wydajność zasilacza / Netzgerät	
Peso netto / Net weight / Waga netto / Nettogewicht	5,2kg

*Corporate research


EAN 5908266100012 (W)

EAN 5908266100067 (WW)





Certified in accordance with:

EN60598-1:2008+A11	LVD 2006/95/EC
EN60598-2-1:1989	EN6100-3-2/A2
EN60598-2-5:1998	EN6100-3-3
EN62471:2008	EN61347-2-13
EN62493:2010	EN55015/A2



76.0



196.0