

OPTFL01-50UQ



Faretto LED / LED Flood light
Reflektory LED / LED - Scheinwerfer

CE RoHS UL FC

IT / ENG / PL / DE	
Consumo LED / LED power / Zużycie energii LED / LED-Leistung	50W
Consumo / Power consumption / Zużycie energii / Energieverbrauch	60W
Voltaggio / Input voltage & frequency	85-265VAC, 50/60 Hz
Napięcie wejściowe i częstotliwość / Eingangsspannung und Frequenz	
Fattore di potenza / Power factor / Współczynnik mocy / Leistungsfaktor	> 0,9
Tipo LED / LED Type / Typ LED / Typ von LED	Epistar
Efficienza dei LED / LED efficiency	90Lm/W
Wydajność LED / Leistungsfähigkeit von LED	
Nr. Led / LED quantity / Ilość LED / Menge von LED	1
Lumen / Total Lumens	4500Lm
Całkowita ilość lumenów / Gesamte Menge von Lumen	
Materiali e finiture / Materials and finishing	Lega di alluminio + vetro temperato / Aluminum alloy + tempered glass / Stop aluminium + szkło hartowane / Cast Aluminum + Glas
Materiały i wykończenie / Materialien und Ausfertigung	Argento / Silver / Srebro / Silber
Colore / Product color / Kolor produktu / Farbe des Fabrikats	
Temperatura della luce / Color temperature	2700-3000K / 4000-4500K / 5500-6000K
Temperatura barwowa / Farbtemperatur	
CRI / Color Rendering Index	80
Współczynnik oddawania barw / Farbwiedergabeindex	
Durata / Lifetime / Czas użytkowania / Lebensdauer	> 50.000 h
Riciclabile / Recycling / Recycling / Recykling	Sì / yes / tak / ja
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	IP65
Temperatura di funzionamento / Operating temperature	-15°C~+55°C
Temperatura pracy / Arbeitstemperatur	
Dimensioni / Product dimensions	290x108x240mm
Wymiary produktu / Abmessungen des Fabrikats	
Peso netto / Net weight / Waga netto / Nettogewicht	~2,8kg

*Corporate research

Handle with the possibility of adjusting the angle of inclination of the lamp.