

OPTHB02BT-40



LED High Bay



IT / ENG / PL / DE	
Consumo / Power consumption / Zużycie energii / Energieverbrauch	40W
Voltaggio / Input voltage & frequency	90-305VAC, 50/60Hz
Napięcie wejściowe i częstotliwość / Eingangsspannung und Frequenz	
Fattore di potenza / Power factor / Współczynnik mocy / Leistungsfaktor	> 0,96
Tipo LED / LED type / Typ LED / Typ von LED	COB
Temperatura della luce / Color temperature	
Temperatura barwowa / Farbtemperatur	4000K / 5000K / 5700K
Angolo di proiezione / Beam angle	
Kąt rozsyłu światła / Lichtverteilungswinkel	60°
Durata / Lifetime / Czas użytkowania / Lebensdauer	> 40.000 h
Riciclabile / Recycling / Recycling / Recykling	Sì / yes / tak / ja
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	IP40
Temperatura di funzionamento / Operating temperature	
Temperatura pracy / Arbeitstemperatur	-20°C~+50°C
Temperatura di magazzino / Storage temperature	
Temperatura składowania / Aufbewahrungstemperatur	-20°C~+60°C
Colore / Product color / Kolor produktu / Farbe des Fabrikats	Argento / silver / srebrny / silber
Materiali e finiture / Materials and finishing	Aluminum + PC / Alluminio + PC /
Materiały i wykończenie / Materialien und Ausfertigung	Aluminium + PC / Aluminum + PC
Dimensioni / Product dimensions	
Wymiary produktu / Abmessungen des Fabrikats	Ø300x230mm
Lumen / Total Lumens	
Całkowita ilość lumenów / Gesamte Menge von Lumen	4400Lm
CRI / Color Rendering Index	
Współczynnik oddawania barw / Farbwiedergabeindex	> 85
Opzioni / Options / Opcje / Varianten	Regolazione della luminosità / dimming / przyciemnianie / Dimmermöglichkeit
Peso netto / Net weight / Waga netto / Nettogewicht	~1,3kg

*Corporate research

Certified in accordance with:

EN60598-1:2008+A11	LVD 2006/95/EC
EN60598-2-1:1989	EN6100-3-2/A2
EN60598-2-5:1998	EN6100-3-3
EN62471:2008	EN61347-2-13
EN62493:2010	EN55015/A2



Meanwell Driver

Dimensions[mm]:

