

OPTPRJ02LT-180




Faretto LED / LED Flood light
Reflektory LED / LED - Scheinwerfer



IT / ENG / PL / DE	
Consumo LED / LED power / Zużycie energii LED / LED-Leistung	180W
Consumo / Power consumption / Zużycie energii / Energieverbrauch	200W
Voltaggio / Input voltage & frequency	90-305 VAC, 50/60 Hz
Napięcie wejściowe i częstotliwość / Eingangsspannung und Frequenz	
Tipo LED / LED type / Typ LED / Typ von LED	CREE
Nr. LED / LED quantity / Ilość LED / Menge von LED	30
Temperatura della luce / Color temperature	3000-7000K
Temperatura barwowa / Farbtemperatur	
Angolo di proiezione / Beam angle	5° (±2,5°)
Kąt rozsyłu światła / Lichtverteilungswinkel	
Durata / Lifetime / Czas użytkowania / Lebensdauer	50.000h
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	IP65
Colore / Product color / Kolor produktu / Farbe des Fabrikats	Nero / bianco / grigio Black / white / grey Czarny / biały / szary Schwarz / weiß / grau
Materiali e finiture / Materials and finishing Materiały i wykończenie/ Materialien und Ausfertigung	Lega di alluminio + vetro temperato / Aluminum alloy + tempered glass / Stop aluminium + szkło hartowane / Cast Aluminium + Glas
Temperatura di funzionamento / Operating temperature	-40°C~+45°C
Temperatura pracy / Arbeitstemperatur	
Dimensioni / Product dimensions	335x345x479mm
Wymiary produktu / Abmessungen des Fabrikats	
Lumen / Total Lumens	13600Lm
Całkowita ilość lumenów / Gesamte Menge von Lumen	
CRI / Color Rendering Index	> 75
Współczynnik oddawania barw / Farbwiedergabeindex	
Opzioni / Options / Opcje / Varianten	Oscuramento / dimming / przyciemnianie / verdunklung
Peso netto / Net weight / Waga netto / Nettogewicht	~16kg

*Corporate research

Illumination data:



Certified in accordance with:

EN60598-1:2008+A11	LVD 2006/95/EC
EN60598-2-1:1989	EN6100-3-2/A2
EN60598-2-5:1998	EN6100-3-3
EN62471:2008	EN61347-2-13
EN62493:2010	EN55015/A2

Dimensions [mm]:

