

# OPTPRJ02LT-60




Faretto LED / LED Flood light  
Reflektory LED / LED - Scheinwerfer



IT / ENG / PL / DE	
Consumo LED / LED power / Zużycie energii LED / LED-Leistung	60W
Consumo / Power consumption / Zużycie energii / Energieverbrauch	70W
Voltaggio / Input voltage & frequency	90-305 VAC, 50/60 Hz
Napięcie wejściowe i częstotliwość / Eingangsspannung und Frequenz	
Tipo LED / LED type / Typ LED / Typ von LED	<b>CREE</b>
Nr. LED / LED quantity / Ilość LED / Menge von LED	12
Temperatura della luce / Color temperature	3000-7000K
Temperatura barwowa / Farbtemperatur	
Angolo di proiezione / Beam angle	5° (±2,5°)
Kąt rozsyłu światła / Lichtverteilungswinkel	
Durata / Lifetime / Czas użytkowania / Lebensdauer	50.000h
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	IP65
Colore / Product color / Kolor produktu / Farbe des Fabrikats	Nero / bianco / grigio Black / white / grey Czarny / biały / szary Schwarz / weiß / grau
Materiali e finiture / Materials and finishing Materiały i wykończenie / Materialien und Ausfertigung	Lega di alluminio + vetro temperato / Aluminum alloy + tempered glass / Stop aluminium + szkło hartowane / Cast Aluminium + Glas
Temperatura di funzionamento / Operating temperature	-40°C~+45°C
Temperatura pracy / Arbeitstemperatur	
Dimensioni / Product dimensions	249x288x463mm
Wymiary produktu / Abmessungen des Fabrikats	
Lumen / Total Lumens	4800Lm
Całkowita ilość lumenów / Gesamte Menge von Lumen	
CRI / Color Rendering Index	> 75
Współczynnik oddawania barw / Farbwiedergabeindex	
Opzioni / Options / Opcje / Varianten	Oscuramento / dimming / przyciemnianie / verdunklung
Peso netto / Net weight / Waga netto / Nettogewicht	~10kg

\*Corporate research

### Illumination data:



Certified in accordance with:

- EN60598-1:2008+A11 LVD 2006/95/EC
- EN60598-2-1:1989 EN6100-3-2/A2
- EN60598-2-5:1998 EN6100-3-3
- EN62471:2008 EN61347-2-13
- EN62493:2010 EN55015/A2

### Dimensions [mm]:

