


OPTPRK01WK-30W



Lampioni / LED park light
Oświetlenie parkowe LED / LED - Parkbeleuchtung

CE RoHS




IP66

Class II

IT / ENG / PL / DE	
Consumo / Power consumption / Zużycie energii / Energieverbrauch	32W
Fattore di potenza / Power factor / Współczynnik mocy / Leistungsfaktor	95%
Efficienza dei LED / LED efficiency	120 lm/W
Wydajność LED / Leistungsfähigkeit von LED	
Equivalente a / Equivalent lamp power	30W ≈ 150W
Ekwiwalentna moc / Äquivalente Leistung	
Tipo LED / LED type / Typ LED / Typ von LED	CREE LED
Temperatura della luce / Color temperature	2700K - 4000K - 5500K
Temperatura barwowa / Farbtemperatur	
Angolo di proiezione / Beam angle	120x120°
Kąt rozsyłu światła / Lichtverteilungswinkel	
Durata / Lifetime / Czas użytkowania / Lebensdauer	> 50.000 h
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	IP66
Temperatura di funzionamento / Operating temperature	-30°C ~ 50°C
Temperatura pracy / Arbeitstemperatur	
Materiali e finiture / Materials and finishing	Aluminum alloy + glass (PMMA) / Lega di alluminio + vetro o (PC) / Stop aluminium + szkło lub (PC) / Cast Aluminium + Glas (PC)
Materiały i wykończenie / Materialien und Ausfertigung	
Energy label / Energy label	A*
Etykieta energetyczna / Energieverbrauchskennzeichnung	
Dimensioni / Product dimensions	Ø460x617mm
Wymiary produktu / Abmessungen des Fabrikats	
Lumen / Total Lumens	2500 lm
Całkowita ilość lumenów / Gesamte Menge von Lumen	
CRI / Color Rendering Index	CRI > 80
Współczynnik oddawania barw / Farbwiedergabeindex	
Peso netto / Net weight / Waga netto / Nettogewicht	10,0 kg

*Corporate research



Certified in accordance with:

EN60598-1:2008+A11	LVD 2006/95/EC
EN60598-2-1:1989	EN61000-3-2:2006+A1/A2:2009
EN60598-2-5:1998	EN61000-3-3:2008
EN62471:2008	EN61347-2-13
EN62493:2010	EN55015:2006+A1:2007+A2:2009
EN61547:2009	EMC 2004/108/EC