

OPTST02-G60



Lampade stradali LED / LED Street light
Lampy uliczne LED / LED - Straßenbeleuchtung



RoHS



IT / ENG / PL / DE

Efficienza dei LED / LED efficiency	105 Lm/W (130 Lm/W CREE)
Wydajność LED / Leistungsfähigkeit von LED	60X1W LED
Nr. Led / LED quantity / Ilość LED / Menge von LED	HP
Tipo LED / LED type / Typ LED / Typ von LED	3000-3500K/4000-4500K/5000-7000K
Temperatura della luce / Color temperature	50.000 h
Temperatura barwowa / Farbtemperatur	Si / yes / tak / ja
Durata / Lifetime / Czas użytkowania / Lebensdauer	66
Riciclabile / Recycling / Recycling / Recykling	09
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	0%
IK Protezione agli urti / IK rating / Stopień ochrony IK / Schutzart IK	-40°C~45°C
ULOR	-40°C~60°C
Temperatura di funzionamento / Operating temperature	Lega di alluminio + vetro temperato / Aluminum alloy + tempered glass / Stop aluminium + szkło hartowane / Cast Aluminum + Glas
Temperatura pracy / Arbeitstemperatur	Argento+Nero / silver+black / srebrny+czarny / silber+schwarz,
Temperatura di magazzino / Storage temperature	Argento / Silver / Srebro / Silber – RAL 7024
Temperatura stowienia / Aufbewahrungstemperatur	A*
Materiali e finiture / Materials and finishing	Fotocellula, pannello solare, turbina eolica, a distnza/ Photocell, solar battery, air turbine, remote control / fotokomórka, bateria słoneczna, turbina powietrzna, zdalne sterowanie / fotozelle, solarbatterie, windturbine, fernsteuerung
Materialy i wykończenie / Materialien und Ausfertigung	
Colore / Product color / Kolor produktu / Farbe des Fabrikats	
Energy label / Energy label	
Etykieta energetyczna / Energieverbrauchskennzeichnung	
Accessori / Accessories / Akcesoria / Zubehör	

*Corporate research

Certified in accordance with:

EN60598-1:2008+A11	LVD 2006/95/EC
EN60598-2-1:1989	EN6100-3-2/A2
EN60598-2-5:1998	EN6100-3-3
EN62471:2008	EN61347-2-13
EN62493:2010	EN55015/A2