

# OPTFL04-28



illuminazione LED per le gallerie / LED Tunnel light  
Oświetlenie tunelowe LED / LED - Tunnelbeleuchtung

RoHS   

IT / ENG / PL / DE	OPTFL04-28
Consumo / Power consumption / Zużycie energii / Energieverbrauch	30W
Voltaggio / Input voltage & frequency	AC100~277V 50~60Hz
Napięcie wejściowe i częstotliwość / Eingangsspannung und Frequenz	
Fattore di potenza / Power factor / Współczynnik mocy / Leistungsfaktor	> 90%
Efficienza dei LED / LED efficiency	110~130 Lm/W
Wydajność LED / Leistungsfähigkeit von LED	
Nr. Led / LED quantity / Ilość LED / Menge von LED	28x1W LED
Tipo LED / LED type / Typ LED / Typ von LED	HP
Temperatura della luce / Color temperature	3000-3500K/4000-4500K/5000-7000K/7000K
Temperatura barwowa / Farbtemperatur	
Angolo di proiezione / Beam angle	130°x80°
Kąt rozsyłu światła / Lichtverteilungswinkel	
Durata / Lifetime / Czas użytkowania / Lebensdauer	50.000 h
Riciclabile / Recycling / Recycling / Recykling	Sì / yes / tak / ja
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	65
IK Protezione agli urti / IK rating / Stopień ochrony IK / Schutzart IK	09
ULOR	0%
Temperatura di funzionamento / Operating temperature	-40°C~45°C
Temperatura pracy / Arbeitstemperatur	
Temperatura di magazzino / Storage temperature	-40°C~60°C
Temperatura di stoccaggio / Aufbewahrungstemperatur	
Materiali e finiture / Materials and finishing	Aluminum alloy + glass / Laga di alluminio + vetro
Materialy i wykończenie / Materialien und Ausfertigung	temperato / Stop aluminium + szkło hartowane / Cast Aluminum + Glas
Energy label / Energy label	A*
Etykieta energetyczna / Energieverbrauchskennzeichnung	
Dimensioni / Product dimensions	266x209x252mm
Wymiary produktu / Abmessungen des Fabrikats	
Lumen / Total Lumens	2900Lm
Całkowita ilość lumenów / Gesamte Menge von Lumen	
CRI / Color Rendering Index	Ra > 75
Współczynnik oddawania barw / Farbwiedergabeindex	
Peso netto / Net weight / Waga netto / Nettogewicht	3,59kg

\*Corporate research

EAN 5908266100005 (W)

EAN 5908266100449 (WW)