

OPTFL04-56



Illuminazione LED per le gallerie / LED Tunnel light
Oświetlenie tunelowe LED / LED - Tunnelbeleuchtung

RoHS   

OPTFL04-56	
Consumo / Power consumption / Zużycie energii / Energieverbrauch	65W
Voltaggio / Input voltage & frequency	AC100~277V 50~60Hz
Napięcie wejściowe i częstotliwość / Eingangsspannung und Frequenz	
Fattore di potenza / Power factor / Współczynnik mocy / Leistungsfaktor	> 90%
Efficienza dei LED / LED efficiency	
Wydajność LED / Leistungsfähigkeit von LED	110~130 Lm/W
Nr. Led / LED quantity / Ilość LED / Menge von LED	56x1W LED
Tipo LED / LED type / Typ LED / Typ von LED	HP
Temperatura della luce / Color temperature	
Temperatura barwowa / Farbtemperatur	3000-3500K/4000-4500K/5000-7000K/7000K
Angolo di proiezione / Beam angle	
Kąt rozsyłu światła / Lichtverteilungswinkel	130°x80°
Durata / Lifetime / Czas użytkowania / Lebensdauer	50.000 h
Riciclabile / Recycling / Recycling / Recykling	Sì / yes / tak / ja
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	65
IK Protezione agli urti / IK rating / Stopień ochrony IK / Schutzart IK	09
ULOR	0%
Temperatura di funzionamento / Operating temperature	-40°C~45°C
Temperatura pracy / Arbeitstemperatur	
Temperatura di magazzino / Storage temperature	
Temperatura składowania / Aufbewahrungstemperatur	-40°C~60°C
Materiali e finiture / Materials and finishing	Aluminum alloy + glass / Laga di alluminio + vetro
Materiały i wykończenie/ Materialien und Ausfertigung	temperato / Stop aluminium + szkło hartowane / Cast Aluminum + Glas
Energy label / Energy label	A*
Etykieta energetyczna / Energieverbrauchskennzeichnung	
Dimensioni / Product dimensions	444x209x252mm
Wymiary produktu / Abmessungen des Fabrikats	
Lumen / Total Lumens	5500Lm
Całkowita ilość lumenów / Gesamte Menge von Lumen	
CRI / Color Rendering Index	Ra > 75
Współczynnik oddawania barw / Farbwiedergabeindex	
Peso netto / Net weight / Waga netto / Nettogewicht	5,95kg

*Corporate research

EAN 5908266101484 (W)

EAN 5908266101491 (WW)

