

OPTWL02SQ-2x6KP

Plafoniere a muro LED / LED Wall & ceiling mounted lights

Kinkiety zewnętrzne LED / LED Außenwandlampen






IT / ENG / PL / DE


Consumo / Power consumption / Zużycie energii / Energieverbrauch	12W
Voltaggio / Input voltage & frequency	100-240VAC, 50/60Hz
Napięcie wejściowe i częstotliwość / Eingangsspannung und Frequenz	Nichia
Tipo LED / LED type / Typ LED / Typ von LED	2000-6000K
Temperatura della luce / Color temperature	50.000h
Temperatura barwowa / Farbtemperatur	Si / yes / tak / ja
Durata / Lifetime / Czas użytkowania / Lebensdauer	65
Riciclabile / Recycling / Recykling / Recykling	18x25° / 25x25° / 40x40°
IP Protezione alle infiltrazioni / IP rating / Stopień ochrony IP / Schutzart IP	-20°C~ +40°C
Angolo di proiezione / Beam angle	Lega di alluminio + PC / Aluminum + PC / Stop aluminium + PC / Cast Aluminum + PC
Kąt rozsyłu światła / Lichtverteilungswinkel	Jet black – RAL 9005
Temperatura di funzionamento / Operating temperature	Grey brown – RAL 8019
Temperatura pracy / Arbeitstemperatur	Silver resistand – RAL 9006
Materiali e finiture / Materials and finishing	A*
Materiały i wykończenie / Materialien und Ausfertigung	130x100x90mm
Colore / Product color / Kolor produktu / Farbe des Fabrikats	
Energy label / Energy label	
Etykieta energetyczna / Energieverbrauchskennzeichnung	
Dimensioni / Product dimensions	
Wymiary produktu / Abmessungen des Fabrikats	

*Corporate research


Photometric data:



Light distribution:



Dimensions [mm]:



Certified in accordance with:

EN60598-1:2008+A11	LVD 2006/95/EC
EN60598-2-1:1989	EN61000-3-2:2006+A1/A2:2009
EN60598-2-5:1998	EN61000-3-3:2008
EN62471:2008	EN61347-2-13
EN62493:2010	EN55015:2006+A1:2007+A2:2009
EN61547:2009	EMC 2004/108/EC


Available body color:



Grey brown
RAL 8019



Jet black
RAL 9005



Silver resistand
RAL 9006